


650 TV Line Security Cameras with IR Illuminators

- Horizontal resolution of 650 TVL (normal mode)
- High sensitivity
- Built-in IR illuminators
- 3.7x varifocal lens
- True Day/Night function



KEY FEATURES

- Built-in IR (infrared) illuminators to assist capturing objects in the dark even under 0 lx, up to 16 m (52 feet) away



OFF



ON


- High resolution (650 TV lines in normal mode, 700 horizontal TV lines in sharp mode) and high sensitivity (Color: 0.06 lx, B/W: 0 lx at F1.2 and 50 IRE) achieved by an 1/3-type "EXview HAD CCD II" sensor and Sony's new digital signal processor, "Effio-E"
EXviewHAD CCD II™
- 3.7x variable focal length lens with a focal length of 2.8 mm to 10.5 mm and a horizontal angle of view of 101.8° to 27.4°
- True Day/Night function to switch to Day or Night mode depending on the light level
- Dip SW Control for easy mode setting

- ATR-Lite (Adaptive Tone Reproduction Lite) to compensate for gradation of subjects to an optimum level
- iBLC to compensate for exposure levels in dark scenes to improve subject visibility
- ATW (Automatic Tracing White) and ATW-PRO which automatically adjust the camera's white balance to adapt to sudden changes in lighting conditions
- Internal lock, and line lock selectable
- 2D noise reduction employed
- AC 24 V/DC 12 V operation (±10%)

SPECIFICATIONS

	SSC-CB561R
Camera	
Image Sensor	1/3-type 960H EXview HAD CCD II
Image Sensor (Number of Effective Pixels)	Approx. 0.57 Megapixels
Signal System	PAL
Minimum Illumination (50 IRE)	Color: 0.06 lx (F1.2 AGC ON), B/W: 0 lx (F1.2 AGC ON)
Minimum Illumination (30 IRE)	Color: 0.04 lx (F1.2 AGC ON), B/W: 0 lx (F1.2 AGC ON)
S/N Ratio	More than 55 dB (AGC OFF)
Gain	Auto (ON/OFF)
Shutter Speed	Fixed (1/50 s)
Sync System	Internal/AC line lock selectable
White Balance	ATW (2000K to 10000K), ATW-pro (2500K to 6000K)
Lens	Vari-focal type
Powered Zoom	No
Zoom Ratio	Optical 3.7x
Powered Focus	No
Horizontal Viewing Angle	101.8° to 27.4°
Vertical Viewing Angle	73.7° to 20.6°
Focal Length	f=2.8 mm to 10.5 mm
F-Number	F1.2 (Wide), F2.7 (Tele)
Minimum Object Distance	300 mm
Horizontal Resolution	650 TVL (normal mode), 700 TVL (sharp mode)
Infrared Illuminators	10 pcs
Infrared Irradiation Distance	16 m at 50 IRE
Camera Features	
Day/Night	Yes (True D/N)
Image Enhancement	Yes (ATR-Lite, ON/OFF)
Noise Reduction	Yes (2DNR, ON/OFF)
General	
Power Requirements	AC 24 V ±10%, DC 12 V ±10%
Power Consumption	4.4 W max.
Operating Temperature	-10°C to +50°C (14°F to 122°F)
Storage Temperature	-40 °C to +60 °C (-40°F to +140°F)
Operating Humidity	20% to 80%
Storage Humidity	20% to 95%
Vandal Resistant	No
Dimensions	63 mm x 57 mm x 127 mm (2 1/2 inches x 2 1/4 inches x 5 inches)
Mass	200 g (7.1 oz)
Safety Regulations	EN55022 (Class A) + EN50130-4 EN55022 (Class A) + EN55024 AS/NZS CISPR22 (EN55022) Class A IEC60065 GOST-R IEC60065 compliance
Ingress Protection	No
Supplied Accessories	Operation instructions (1)

DIMENSIONS



Unit: mm (inches)

Distributed by

© 2012 Sony Corporation. All rights reserved.
 Reproduction in whole or in part without written permission is prohibited.
 Features and specifications are subject to change without notice.
 The values for weight and dimension are approximate.
 "Sony", "make.believe", "Effio-E", and "EXview HAD CCD II" are
 trademarks of Sony Corporation.
 All other trademarks are the property of their respective owners.